

Suspended Substrate Stripline Low Pass Filter Catalog

(Version: 2011)

Part Number	3dB Cut off	1dB Pass Band	Insertion Loss	VSWR	Stop Band Attenuation	Power	Connectors	Size (LxWxH)
	GHz	GHz	dB Typ.	Typ.	dB @ GHz, Typ.	W	Typ.	mm
WT-A0148-LS	1	DC~0.9	≤1.0	≤2.0	≥50@1.2~4	15	SMA-F	120x41x10
WT-A0098-LS	2	DC~1.8	≤1.0	≤2.0	≥50@2.3~6	15	SMA-F	53x36x10
WT-A0106-LS	3	DC~2.7	≤1.0	≤2.0	≥50@3.45~8	15	SMA-F	41x34x10
WT-A0149-LS	4	DC~3.6	≤1.0	≤2.0	≥50@4.6~10	15	SMA-F	39x27x10
WT-A0150-LS	5	DC~4.5	≤1.0	≤2.0	≥50@5.8~12	15	SMA-F	35x24x10
WT-A0137-LS	6	DC~5.4	≤1.0	≤2.0	≥50@6.9~14	15	SMA-F	35x22x10
WT-A0151-LS	7	DC~6.3	≤1.0	≤2.0	≥50@8~15	15	SMA-F	33x22x10
WT-A0152-LS	8	DC~7.2	≤1.0	≤2.0	≥50@9.2~16	15	SMA-F	33x21x10
WT-A0079-LS	9	DC~8.1	≤1.0	≤2.0	≥50@10.4~16.5	15	SMA-F	25x19x10
WT-A0153-LS	10	DC~9	≤1.0	≤2.0	≥50@11.5~17	15	SMA-F	24x18.5x10
WT-A0154-LS	11	DC~9.9	≤1.0	≤2.0	≥50@12.5~17.5	15	SMA-F	23x18.5x10
WT-A0155-LS	12	DC~10.8	≤1.0	≤2.0	≥50@13.8~18	15	SMA-F	20x18x10
WT-A0229-LS	13	DC~11.7	≤1.0	≤2.0	≥50@15~19	15	SMA-F	20x17.5x10
WT-A0224-LS	14	DC~12.6	≤1.0	≤2.0	≥50@16.1~20	15	SMA-F	19x17.5x10
WT-A0173-LS	----	DC~2	≤1.0	≤2.0	≥55@2.5~13	15	SMA-F	83x35x10
WT-A0071-LS	----	DC~2.75	≤1.6	≤1.7	≥45@3~8.5	15	SMA-F	59x39x10