

Suspended Stripline High Pass Filter Series (CS Broadband)

(Version: 2017)

Part Number	Cut off Freq.	Pass Band Freq.	Insertion Loss	VSWR	Stop Band Attenuation	Power	Connectors	Size (LxWxH)
	GHz	GHz	dB Typ.	Typ.	dB @ GHz	W	Typ.	mm
WT-A3314-HS	1.0	1.0~10	≤1.0	≤1.5:1	≥50@DC~0.78	15	SMA-Female	61x23x10
WT-A3315-HS	1.25	1.25~12	≤1.0	≤1.5:1	≥50@DC~0.98	15	SMA-Female	52x20.5x10
WT-A3316-HS	1.5	1.5~14	≤1.0	≤1.5:1	≥50@DC~1.17	15	SMA-Female	46x20x10
WT-A3317-HS	1.75	1.75~17	≤1.0	≤1.5:1	≥50@DC~1.38	15	SMA-Female	40x18x10
WT-A3318-HS	2.0	2.0~19	≤1.0	≤1.5:1	≥50@DC~1.58	15	SMA-Female	37x18x10
WT-A3319-HS	2.25	2.25~19	≤1.0	≤1.5:1	≥50@DC~1.77	15	SMA-Female	35x17.5x10
WT-A3320-HS	2.5	2.5~20	≤1.0	≤1.5:1	≥50@DC~1.98	15	SMA-Female	35x17x10
WT-A3321-HS	2.75	2.75~21	≤1.0	≤1.5:1	≥50@DC~2.2	15	SMA-Female	33x17x10
WT-A3322-HS	3.0	3.0~21	≤1.0	≤1.5:1	≥50@DC~2.36	15	SMA-Female	31x16.5x10
WT-A3323-HS	3.25	3.25~22	≤1.0	≤1.5:1	≥50@DC~2.57	15	SMA-Female	30x16.5x10
WT-A3324-HS	3.5	3.5~23	≤1.0	≤1.5:1	≥50@DC~2.77	15	SMA-Female	28x16x10
WT-A3325-HS	3.75	3.75~23	≤1.0	≤1.5:1	≥50@DC~3.03	15	SMA-Female	26x16x10
WT-A3326-HS	4.0	4.0~23	≤1.0	≤1.5:1	≥50@DC~3.2	15	SMA-Female	25x16x10
WT-A3327-HS	4.25	4.25~23	≤1.0	≤1.5:1	≥50@DC~3.4	15	SMA-Female	24x16x10
WT-A3328-HS	4.5	4.5~23.5	≤1.0	≤1.5:1	≥50@DC~3.55	15	SMA-Female	24x16x10
WT-A3329-HS	5.0	5.0~24	≤1.0	≤1.5:1	≥50@DC~4.0	15	SMA-Female	23x16x10
WT-A3330-HS	5.5	5.5~24.5	≤1.0	≤1.5:1	≥50@DC~4.5	15	SMA-Female	22x16x10
WT-A3331-HS	6.0	6.0~24.5	≤1.0	≤1.5:1	≥50@DC~4.9	15	SMA-Female	22x16x10
WT-A3332-HS	6.5	6.5~25	≤1.0	≤1.5:1	≥50@DC~5.4	15	SMA-Female	21x15x10
WT-A3333-HS	7.0	7.0~26	≤1.0	≤1.5:1	≥50@DC~5.85	15	SMA-Female	20x15x10

WT Microwave INC.

<http://www.wtmicrowave.com> E-mail: tech@wtmicrowave.com sales@wtmicrowave.com

TEL:+86-28-84300332/84300037 FAX:+86-28-84300332-807

Add: Chengdu of China Zip Code:610051

D	P
----------	----------

WT-A2832-HS	7.5	7.5~27	≤1.0	≤1.5:1	≥50@DC~6.25	15	SMA-Female	20x15x10
WT-A3334-HS	8.0	8.0~28	≤1.0	≤1.5:1	≥50@DC~6.65	15	SMA-Female	19x15x10
WT-A3335-HS	8.5	8.5~28	≤1.0	≤1.5:1	≥50@DC~7.1	15	SMA-Female	19x15x10
WT-A3011-HS	9.0	9.0~28	≤1.0	≤1.5:1	≥50@DC~7.45	15	SMA-Female	19x15x10
WT-A3336-HS	9.5	9.5~28	≤1.0	≤1.5:1	≥50@DC~7.93	15	SMA-Female	19x15x10
WT-A3337-HS	10	10~28	≤1.0	≤1.5:1	≥50@DC~8.25	15	SMA-Female	19x15x10
WT-A3338-HS	10.5	10.5~28	≤1.0	≤1.6:1	≥50@DC~8.5	15	SMA-Female	15x12.7x10
WT-A3338-HS	10.5	10.5~40	≤1.0	≤1.8:1	≥50@DC~8.5	15	2.92mm-Female	15x12.7x10
WT-A3339-HS	11	11~28	≤1.0	≤1.6:1	≥50@DC~9.0	15	SMA-Female	15x12.7x10
WT-A3339-HS	11	11~40	≤1.0	≤1.8:1	≥50@DC~9.0	15	2.92mm-Female	15x12.7x10
WT-A3340-HS	11.5	11.5~28	≤1.0	≤1.6:1	≥50@DC~9.3	15	SMA-Female	15x12.7x10
WT-A3340-HS	11.5	11.5~40	≤1.0	≤1.8:1	≥50@DC~9.3	15	2.92mm-Female	15x12.7x10
WT-A3341-HS	12	12~28	≤1.0	≤1.6:1	≥50@DC~9.6	15	SMA-Female	15x12.7x10
WT-A3341-HS	12	12~40	≤1.0	≤1.8:1	≥50@DC~9.6	15	2.92mm-Female	15x12.7x10
WT-A3141-HS	18	18~40	≤1.0	≤1.8:1	≥50@DC~15	15	2.92mm-Female	12.7x12.7x10
WT-A3141-HS	18	18~28	≤1.0	≤1.8:1	≥50@DC~15	15	SMA-Female	12.7x12.7x10