

WT-A10335-BLC

LC Band Pass Filter

Technical Data Sheet

S/N	Item	Parameters
1	Center Frequency(F0)	240MHz
2	3.0dB Bandwidth	40MHz (220 ~ 260MHz) [Deviation: $\pm 10\text{MHz}$ @ Temperature Range: $+20^{\circ}\text{C} \sim +30^{\circ}\text{C}$]
3	Insertion Loss @ F0	$\leq 4.0\text{dB}$ @ 240MHz
4	VSWR	$\leq 1.5:1$ @ 230 ~ 250MHz
5	Stop Band Rejection	$\geq 70\text{dB}$ @ DC ~ 120MHz $\geq 70\text{dB}$ @ 480 ~ 800MHz
6	Impedance	50 Ohms
7	Power Handling	1.0W Max.
8	Connectors	SMA-Female
9	Surface Finish	Painted Black
10	Temperature Range	$-30^{\circ}\text{C} \sim +70^{\circ}\text{C}$
11	Material	Housing: 6061 Aluminum alloy Connectors: Stainless Steel Cover: LY12 Aluminum alloy Other screw: Stainless Steel
12	Dimensions	40*18*13mm
13	Net weight	0.025 KG

Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: $\pm 0.3\text{mm}$)

