

WT-A3063-Q05

腔体带通滤波器

技术指标

Serial	Parameters	
1	中心频率(Center Frequency)[F0]	468MHz
2	带宽(Bandwidth)	$\pm 5\text{MHz}$ (463~473MHz)
3	插入损耗(Insertion Loss)	$\leq 1.0\text{dB}$
4	回波损耗(Return Loss)	$\geq 18\text{dB}$
5	带外抑制(Rejection)	$\geq 40\text{dB}$ @ $F0 \pm 20\text{MHz}$ (DC~448MHz、488~1000MHz)
6	功率(Power)	$\leq 20\text{W}$
7	阻抗(Impedance)	50 ohms
8	表面处理(Surface Finish)	黑色烤漆(Black Paint)
9	接口形式(Connectors)	N-Male / N-Female
10	净重(Net Weight)	0.445 KG
11	外形结构图(Configuration)	As Below (Size Unit: mm)



成都微通科技有限公司

Chengdu Microwave Communication Technology CO.,Ltd

http://www.cdweitong.com E-mail:tech@cdweitong.com sales@cdweitong.com

TEL:+86-28-84300332 FAX:+86-28-84300332-807

地址:中国 成都市成华区建材路 37 号 1-1108 610051

ADD: 11F-1108, Building#1, NO.37, Jiancai Road, Chengdu 610051, China. Zip Code:610051

第4页 共4页