

WT-A6422-Q08

Cavity Band Pass Filter

Technical Data Sheet

| S/N | Item | Parameters |
|-----|--------------------------|---|
| 1 | Center Frequency(F0) | 1370MHz |
| 2 | Pass Band Frequency | 1350 ~ 1390MHz |
| 3 | Pass Band Insertion Loss | ≤1.5dB |
| 4 | Pass Band Ripple | ≤0.7dB |
| 5 | Pass Band VSWR | ≤1.22:1 |
| 6 | Stop Band Attenuation | ≥60dB @ DC ~ 1330MHz ≥60dB @ 1410 ~ 5000MHz |
| 7 | Impedance | 50 Ohms |
| 8 | Power Handling | 20W Max. |
| 9 | Connectors | N-Male / N-Female |
| 10 | Surface Finish | Painted Black |
| 11 | Temperature Range | -30°C ~ +70°C |
| 12 | Material | Housing: 6061 Aluminum alloy Resonant column: H59 Copper alloy Cover: LY12 Aluminum alloy Connectors: H59 Copper, Plated ternary alloy Tuning screw: H62 Copper alloy Other screw: Stainless Steel |
| 13 | Dimensions | 120*62*31mm |
| 14 | Net weight | 0.41 KG |

Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

