

WT-A6898-S20

Comb Band Pass Filter

Technical Data Sheet

| S/N | Item | Parameters | | | | | | |
|--------------------------------|------------------------------|--|---------------------------|-----------------------------|--------------------------|------------------------------|--------------------------------|--------------------------|
| 1 | Center Frequency(F0) | 33GHz | | | | | | |
| 2 | Pass Band Frequency | 26 ~ 40GHz | | | | | | |
| 3 | Pass Band Insertion Loss | ≤1.2dB | | | | | | |
| 4 | Pass Band Ripple | ≤0.5dB | | | | | | |
| 5 | Pass Band Return Loss | ≥17dB | | | | | | |
| 6 | Stop Band Rejection | <table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">≥80dB @ DC ~ 24000MHz</td> <td style="width: 50%;">≥35dB @ 41000 ~ 42300MHz</td> </tr> <tr> <td>≥45dB @ 24000 ~ 25000MHz</td> <td>≥80dB @ 42300 ~ 43000MHz</td> </tr> <tr> <td></td> <td>≥40dB @ 43000 ~ 47000MHz</td> </tr> </table> | ≥80dB @ DC ~ 24000MHz | ≥35dB @ 41000 ~ 42300MHz | ≥45dB @ 24000 ~ 25000MHz | ≥80dB @ 42300 ~ 43000MHz | | ≥40dB @ 43000 ~ 47000MHz |
| ≥80dB @ DC ~ 24000MHz | ≥35dB @ 41000 ~ 42300MHz | | | | | | | |
| ≥45dB @ 24000 ~ 25000MHz | ≥80dB @ 42300 ~ 43000MHz | | | | | | | |
| | ≥40dB @ 43000 ~ 47000MHz | | | | | | | |
| 7 | Impedance | 50 Ohms | | | | | | |
| 8 | Power Handling | 5W Max. | | | | | | |
| 9 | Connectors | 2.92mm(K)-Female | | | | | | |
| 10 | Surface Finish | Painted Black | | | | | | |
| 11 | Temperature Range | -30°C ~ +70°C | | | | | | |
| 12 | Material | <table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">Housing: H62 Copper alloy</td> <td style="width: 50%;">Connectors: Stainless Steel</td> </tr> <tr> <td>Cover: H62 Copper alloy</td> <td>Other screw: Stainless Steel</td> </tr> <tr> <td colspan="2">Tuning screw: H62 Copper alloy</td> </tr> </table> | Housing: H62 Copper alloy | Connectors: Stainless Steel | Cover: H62 Copper alloy | Other screw: Stainless Steel | Tuning screw: H62 Copper alloy | |
| Housing: H62 Copper alloy | Connectors: Stainless Steel | | | | | | | |
| Cover: H62 Copper alloy | Other screw: Stainless Steel | | | | | | | |
| Tuning screw: H62 Copper alloy | | | | | | | | |
| 13 | Dimensions | 70*16*9mm | | | | | | |
| 14 | Net weight | 0.075 KG | | | | | | |

Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

