

WT-A6973-S20

Comb Band Pass Filter

Technical Data Sheet

S/N	Item	Parameters						
1	Center Frequency(F0)	32.5GHz						
2	Pass Band Frequency	25 ~ 40GHz						
3	Pass Band Insertion Loss	≤1.0dB						
4	Pass Band Ripple	≤0.45dB						
5	Pass Band Return Loss	≥17dB						
6	Stop Band Rejection	<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">≥80dB @ DC ~ 22.8GHz</td> <td style="width: 50%;">≥30dB @ 41 ~ 41.4GHz</td> </tr> <tr> <td>≥40dB @ 22.8 ~ 24GHz</td> <td>≥40dB @ 41.4 ~ 46GHz</td> </tr> </table>	≥80dB @ DC ~ 22.8GHz	≥30dB @ 41 ~ 41.4GHz	≥40dB @ 22.8 ~ 24GHz	≥40dB @ 41.4 ~ 46GHz		
≥80dB @ DC ~ 22.8GHz	≥30dB @ 41 ~ 41.4GHz							
≥40dB @ 22.8 ~ 24GHz	≥40dB @ 41.4 ~ 46GHz							
7	Impedance	50 Ohms						
8	Power Handling	5W Max.						
9	Connectors	2.92mm(K)-Female						
10	Surface Finish	Painted Black						
11	Temperature Range	-30°C ~ +70°C						
12	Material	<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">Housing: H62 Copper alloy</td> <td style="width: 50%;">Connectors: Stainless Steel</td> </tr> <tr> <td>Cover: H62 Copper alloy</td> <td>Other screw: Stainless Steel</td> </tr> <tr> <td colspan="2">Tuning screw: H62 Copper alloy</td> </tr> </table>	Housing: H62 Copper alloy	Connectors: Stainless Steel	Cover: H62 Copper alloy	Other screw: Stainless Steel	Tuning screw: H62 Copper alloy	
Housing: H62 Copper alloy	Connectors: Stainless Steel							
Cover: H62 Copper alloy	Other screw: Stainless Steel							
Tuning screw: H62 Copper alloy								
13	Dimensions	70*16*9mm						
14	Net weight	0.07 KG						

Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

