

WT-A8960-Q11

Cavity Band Pass Filter

Technical Data Sheet

S/N	Item	Parameters	
1	Center Frequency(F0)	1950MHz	
2	Pass Band Frequency	1900 ~ 2000MHz	
3	Pass Band Insertion Loss	≤1.5dB	
4	Pass Band Ripple	≤0.6dB	
5	Pass Band VSWR	≤1.15:1	
6	Stop Band Rejection	≥80dB @ DC ~ 1825MHz ≥65dB @ 1825 ~ 1850MHz	≥70dB @ 2050 ~ 2060MHz ≥80dB @ 2060 ~ 7500MHz
7	Impedance	50 Ohms	
8	Power Handling	20W Max.	
9	Connectors	SMA-Female	
10	Surface Finish	Painted Black	
11	Temperature Range	-30°C ~ +70°C	
12	Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Resonant column: H59 Copper alloy Connectors: Stainless Steel Other screw: Stainless Steel
13	Dimensions	140*22*24mm	
14	Net weight	0.145 KG	

Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

