

# WT-A9400-J13

## Interdigital Band Pass Filter

### Technical Data Sheet

S/N	Item	Parameters						
1	Center Frequency(F0)	2530MHz						
2	Pass Band Bandwidth	500MHz (2280 ~ 2780MHz)						
3	Pass Band Insertion Loss	≤1.2dB						
4	Pass Band Ripple	≤0.6dB						
5	Pass Band Return Loss	≥14dB						
6	Stop Band Rejection	<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">≥80dB @ DC ~ 2050MHz</td> <td style="width: 50%;">≥50dB @ 2900 ~ 2950MHz</td> </tr> <tr> <td>≥60dB @ 2050 ~ 2150MHz</td> <td>≥70dB @ 2950 ~ 5000MHz</td> </tr> </table>	≥80dB @ DC ~ 2050MHz	≥50dB @ 2900 ~ 2950MHz	≥60dB @ 2050 ~ 2150MHz	≥70dB @ 2950 ~ 5000MHz		
≥80dB @ DC ~ 2050MHz	≥50dB @ 2900 ~ 2950MHz							
≥60dB @ 2050 ~ 2150MHz	≥70dB @ 2950 ~ 5000MHz							
7	Impedance	50 Ohms						
8	Power Handling	5.0W Max.						
9	Connectors	SMA-Male						
10	Surface Finish	Painted Black						
11	Temperature Range	-30°C ~ +70°C						
12	Material	<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">Housing: 6061 Aluminum alloy</td> <td style="width: 50%;">Connectors: Stainless Steel</td> </tr> <tr> <td>Cover: LY12 Aluminum alloy</td> <td>Other screw: Stainless Steel</td> </tr> <tr> <td colspan="2">Tuning screw: H62 Copper alloy</td> </tr> </table>	Housing: 6061 Aluminum alloy	Connectors: Stainless Steel	Cover: LY12 Aluminum alloy	Other screw: Stainless Steel	Tuning screw: H62 Copper alloy	
Housing: 6061 Aluminum alloy	Connectors: Stainless Steel							
Cover: LY12 Aluminum alloy	Other screw: Stainless Steel							
Tuning screw: H62 Copper alloy								
13	Dimensions	89*36*10mm						
14	Net weight	0.07 KG						

Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

