

WT-A9658-Q08

Cavity Band Pass Filter

Technical Data Sheet

S/N	Item	Parameters						
1	Center Frequency(F0)	9.5GHz						
2	Pass Band Frequency	9.0 ~ 10GHz						
3	Pass Band Insertion Loss	≤0.7dB						
4	Pass Band Ripple	≤0.3dB						
5	Pass Band Return Loss	≥23dB						
6	Stop Band Rejection	<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">≥80dB @ DC ~ 7.8GHz</td> <td style="width: 50%;">≥70dB @ 11 ~ 11.2GHz</td> </tr> <tr> <td>≥70dB @ 7.8 ~ 8.0GHz</td> <td>≥80dB @ 11.2 ~ 23GHz</td> </tr> </table>	≥80dB @ DC ~ 7.8GHz	≥70dB @ 11 ~ 11.2GHz	≥70dB @ 7.8 ~ 8.0GHz	≥80dB @ 11.2 ~ 23GHz		
≥80dB @ DC ~ 7.8GHz	≥70dB @ 11 ~ 11.2GHz							
≥70dB @ 7.8 ~ 8.0GHz	≥80dB @ 11.2 ~ 23GHz							
7	Impedance	50 Ohms						
8	Power Handling	10W Max.						
9	Connectors	SMA-Male / SMA-Female						
10	Surface Finish	Painted Black						
11	Temperature Range	-30°C ~ +70°C						
12	Material	<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">Housing: H62 Copper alloy</td> <td style="width: 50%;">Connectors: Stainless Steel</td> </tr> <tr> <td>Cover: H62 Copper alloy</td> <td>Other screw: Stainless Steel</td> </tr> <tr> <td colspan="2">Tuning screw: H62 Copper alloy</td> </tr> </table>	Housing: H62 Copper alloy	Connectors: Stainless Steel	Cover: H62 Copper alloy	Other screw: Stainless Steel	Tuning screw: H62 Copper alloy	
Housing: H62 Copper alloy	Connectors: Stainless Steel							
Cover: H62 Copper alloy	Other screw: Stainless Steel							
Tuning screw: H62 Copper alloy								
13	Dimensions	70*16*9mm						
14	Net weight	0.07 KG						

Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

